


Charles Multi-Purpose Housings (CMPH) Copper/Fiber Enclosures Ordering Guide



- 1** **Flame Retardancy Option**
N = Non-Flame Retardant
F = Flame Retardant
- 2** **Copper Backboard Diameter**
1 = 10" Diameter
- 3** **Fiber Backboard Diameter**
1 = 10" Diameter
- 4** **Copper Backboard Style (see reverse)**
0 = None
U = CPLU Universal Copper Backboard
S = CPLS Copper Splice Bracket
- 5** **Fiber Backboard Style (see reverse)**
C = CFDP-ELS Backboard
E = BDO-ETS Backboard
G = BDO-EG Backboard
I = CFDP-EL Interconnect Backboard
P = BDO5EB/OPT Backboard
T = BDO-ET Backboard
- 6** **Pre-Connectorized Adapter Type (I & P Backboards Only)**
0 = None
A = SC/APC
B = SC/UPC
F = FC
P = Optifit SCA
- 7** **Pre-Connectorized Adapter Quantity (I & P Backboards Only)**
00 = None
02 = Two
08 = Eight
12 = Twelve
18 = Eighteen
24 = Twenty Four
- 8** **Mounting Stakes Option**
0 = No Mounting Stakes
1 = Two 30" UMS Mounting Stakes
2 = Two 36" UMS Mounting Stakes
3 = Two 42" UMS Mounting Stakes



SAMPLE PART NUMBER

CMPH-7F11UIB240


CMPH 7500 Series flame retardant Copper/Fiber Enclosure with 10" CPLU Copper Backboard, 10" CFDP-EL Interconnect Backboard with 24 SP/UPC connectors, and no Mounting Stakes



Charles Multi-Purpose Housings (CMPH) Copper/Fiber Enclosures Ordering Guide


Copper Backboard Styles

CPLU Universal Copper Backboard




Universal backboard for mounting terminal blocks, load coil cases, and other equipment. Rear side of backboard has repositionable ladder bars for attaching cable splice bundles. 900 total pairs splice capacity.

CPLS Copper Splice Bracket




"S" bracket features offset, repositionable ladder bars for attaching cable splice bundles. 1,200 total pairs splice capacity.

Overall Dimensions




Fiber Backboard Styles

CFDP-ELS Backboard




Two compartment backboard (distribution and drop) featuring locking security doors. Total splice capacity of 192 fibers.

BDO5EB/OPT Backboard




Open architecture backboard for co-located copper and fiber. Total splice capacity of 120 fibers. Bulkhead plate included for 8 sealed connectors. Rear side of backboard has ladder bars with 600 pair copper splice capacity.

BDO-EG Backboard




Open architecture backboard has total splice capacity of 168 fibers.

CFDP-EL Interconnect Backboard




Two compartment backboard (central office and drop) featuring locking security doors. Total splice capacity of 120 fibers. Interconnect bulkhead included for up to 24 SC APC/UPC connectors.

BDO-ET Backboard



Open architecture backboard designed to mount sealed fiber terminal blocks (no fiber splice tray provisions).

BDO-ETS Backboard



Open architecture backboard designed to mount sealed fiber terminal blocks. A fiber splice tray holder attached to the rear of the backboard facilitates loop-through splicing and repair. Total splice capacity of 48 fibers.