## **CNUB Power / Fiber Demarcation Enclosure**

#### Ground Mount Shroud Enclosure for Power / Fiber to Small Cells







The CNUB is a single compartment shroud enclosure that houses an 8-position AC load center, an AC surge suppressor, a meter socket, and a Charles CFTT or CFIT-DWDM-3 fiber box (sold separately). The outdoor, weather-resistant CNUB is often used to provide AC power and fiber connections to RRH at small cell locations where pole-mounted enclosures are prohibited or not desired. CNUB are mounted on a compsite mounting pad (Charles CPAD) for quick installation in unpaved areas, often adjacent to a utility/lighting pole with attached radios and an antenna.

Optional 15" Plinths are available to raise the shroud in flood prone areas or for cable slack storage. Up to two plinths can be mounted to the bottom of a CNUB enclosure for an additional 15" or 30" of height.

**Dimensions and Weight:** 42"Hx12"Wx11"D, approx. 73 lbs.

**Construction:** .125" Welded Aluminum,

Powder Coated Finish (Various Colors)

Electrical:

AC Load Center Square D QO816L100RB

Meter Socket CNUB-421211xBA1: Milbank U762-RL-TG, 150A ringless

CNUB-421211xBB1: Milbank U8874RLLR, 125A, ring type CNUB-421211xBC1: Milbank, U7021-RL-TG-KK-BLG, 200A,

ringless with horn bypass Raycap AC2080-02-W

Bonding and Grounding One 2x8-position ground bar

Cable Entrance Bottom of the cabinet

Security: (2) 216-Style Padlockable Quarter Turn Door Latches with Hasps

**Environmental:** 

AC Surge Protector

Operating Temp. Range, Outside Enclosure

-40° to +115°F, -40° to 46°C

-40° to +149°F, -40° to 65°C

Humidity (% RH)

-40° to +149°F, -40° to 65°C

0 to 95% (non-condensing)

Humidity (% RH) 0 to 95% (non-condensing)
Altitude Up to 2,000 meters (6,560')

Optional CPAD Buried Mounting Platform: Part #:CPAD-SAE1211xxx

Composite material construction, 25"x23"x14" outside dim, 20"x14" platform dim., 25 lbs.

**Optional 15" Plinth:** Part #:97-002377x-A



For additional product information, please visit www.charlesindustries.com

OG-OSP064-J19

PAGE 1

Web: www.charlesindustries.com





# **CNUB Power / Fiber Demarcation Enclosure**


### Ground Mount Shroud Enclosure for Power / Fiber to Small Cells


#### **CNUB CONFIGURATIONS & COLOR OPTIONS**

PART NUMBER	COLOR	TOUCH-UP PAINT	OPTIONAL PLINTH KIT
CNUB-421211ABx1	Off White	02-000290-0	97-002377A-A
CNUB-421211DBx1	Gray, RAL7035	02-000629-0	97-002377D-A
CNUB-421211FBx1	Black	02-000611-0	97-002377F-A
CNUB-421211GBx1	National Park Brown	02-000626-0	97-002377G-A
CNUB-421211HBx1	Hunt Club Green	02-000599-0	97-002377H-A









PAGE 2

**CPAD Buried** 

**Mounting Platform** 

for CNUB #CPAD-SAE1211xxx

OG-OSP064-J19

MOUNTING BRACKET FOR CHARLES CFTT

OR CFIT FIBER BOX

www.charlesindustries.com

2X8 POSITION

GROUND BAR