# Fiber Optic Round Closures (FORC)

### Versatile and easy-to-use fiber closures for FTTH networks



Charles fiber optic round closures (FORC) provide a versatile and functional cost-effective solution for FTTH network connections. These compact closures are a space saving solution. They have a feed port and two branch ports. The units are an ideal solution for a repair closure. In addition, the branch ports can be fitted with multi-cable grommets to splice in drops and can be used as a drop closure. These closures are fully sealed units which can be installed to meet any deployment requirement.

#### **Product Features**

- Robust glass filled polypropylene housing
- · Mechanical compression technology provides cost-effective reliable cable sealing
- · Sealed IP68 rated
- Dual feed port and two branch ports
- · Multi-cable grommets available for use as a drop closure
- · 36 fiber splice capacity
- · Compact design for use in limited space applications



Hinged Splice Tray Bracket (storage position)



Dual feed port and two branch ports



Three splice tray capacity, each 12 single fusion splice



Hinged Splice Tray Bracket (service position)



## **Product Specifications**

Dimensions (L x W x H) 11.6" x 8.7" x 3.5" (295mm x 220mm x 90mm)

Weight: 4.4lb. (2kg)

 Ambient Temperature:
 -40°F to 149°F (-40°C to 65°C)

 Feed Cable:
 0.393–0.689 inch (10mm–17.5mm)

 Branch Cable:
 2 ports: 0.315–0.689 inch (8mm–17.5mm)

Drop Port Cable Accommodation: 2 ports, grommets available for 8 - 12mm (0.472"- 0.669")

and 12 - 17mm (0.315" - .472") cables

Multi-cable grommets also available for 4x 5-7mm

or 2x flat drop cable

Splice Capacity: 3 trays, each 12 single fusion splice (total 36 splice)

Cable Sealing Method: Mechanical (compression grommets)


Environmental Rating: IP 68 (2m depth)

Grounding: Optional grounding solution available

#### **Dimensions**

### **Branch Port Grommets**





View	Cable Sizes
0	12 - 17mm (0.472"- 0.669")
0	8 - 12mm (0.315"- 0.472")
600	4x 5 - 7 mm (0.197"- 0.275")
00	2x flat drop (8mm x 4.5mm)

### **Ordering Information**

PART NUMBER DESCRIPTION

FORC36CF5 Fiber Optic Round Closure, Includes three 12 fiber splice trays, Grommet kit for

5-7mm and flat drops, 36 splice protection sleeves.

FORC12DX Fiber Optic Round Closure, layout for use with duct, includes one 12 fiber

splice tray, 12 splice protection sleeves

### Dependable Solutions, Superior Support

- Field-proven and unequaled 24-hour technical support
- Individualized application consultation
- Superior quality (ISO 9001/TL 9000 registered)

#### Visit our website at http://www.charlesindustries.com

Charles Industries, LLC Voice
An Amphenol Company Fax

**Voice:** (847) 806-6300 **Fax:** (847) 806-6231

E-mail: mktserv@charlesindustries.com



An Amphenol Company





D-OSP199-F2