

# Premises Enclosure "Infinity Premises Enclosure" IPE

Infinity Premise Enclosure combine style and easy product installation with our patented True Flex™ Quick Mount feature and Cable Retention slots. The Infinity Premise Enclosure is packed with ergonomic features that ensure reliability and satisfaction.



IPE872-LTC

#### **FEATURES**

- Convenient size in weather resistant high impact thermoplastic alloy
- · Self-latching, hinged cover design snaps closed: with padlock
- Optimize space and cost
- · Quick mount rails enable True Flex devices to be snapped into place
- · Continuous bosses for flexible component placement
- · Cable retention slots allow work to be completed outside of the box

## **IPE Product Specifications**

Outside Dimensions (in/mm)	9.1" × 8.1" × 2.0" (230.4 × 205.0 × 50.8)
Inside Cavity Dimensions (in/ mm)	8.0" x 7.0" x 1.8" (203.4 x 178.1 x 45.2)
Maximum Cubic Foot Print (in/mm)	9.1" x 9.3" x 2.6" 230.4 x 235.4 x 66.1
Bulkhead	1 Port SC/APC (expandable to 3 max)
Impact Test at -40C	5ft/lbs on all surfaces
Drop Test at -40C	5ft onto concrete surface 4 times
High Temperature Storage/ Mold Test	14 days at +75C
Temperature Cycling With Humidity	150 days cycling from -40C to +60C with 95% humidity
UV Resistance (Days Exposed)	60 per ASTMoG26-84
Salt Fog (Days Exposed)	60 per ASTMoBLL7-90
Rain	24 hours at 10psi
Flammability	UL94-5V

#### **MARKETS SERVED:**






Wireless

Broadband Cable



# **IPE Dimension and Images**



Inside cavity measured at the floor of the base Red Green Outside enclosure measured at the rim and

top cover to bottom base

**Black** Overall maximum footprint including latch,

hinges, and bottom mounts

IPE872-LTC Enclosure



Snap-in Fiber Tray



IPE872-LTC Enclosure and Snap-in Fiber Tray





## **Ordering Specification**

**Charles Part Number** 

**Description** 

IPE872-LTC-1SCA

1 SC/APC Port with slack storage

#### Charles Industries, LLC

An Amphenol Company 1450 American Lane, 20th Floor, Schaumburg, IL 60173



mktserv@charlesindustries.com



(847) 806-6300



