

# LiteVu™ Optical Monitoring System

*Optical monitoring increases network uptime and availability, and reduces service time when network issues arise*



LiteVu 1.5RU Chassis



LiteVu 2RU Chassis

Prepared for:



July 2018

The LiteVu Optical Monitoring System is a cost-effective solution for nonintrusive monitoring of power and transmission of an optical link, assisting operators in ensuring the performance and reliability of their optical infrastructure. LiteVu provides a view of network traffic in real time, thus allowing technicians to quickly identify anomalies within the data stream. Slide-in optical tap modules may be added on an as-needed basis to provide “pay-as-you-grow” scalability.

## ***Applications***

- Optical Monitoring of Power and Transmission

## ***Product Specifications***

### **LiteVu 1.5RU Chassis**

Dimensions:	2.5”H x 17”W x 11.5”D (front fiber management tray projects forward additional 5”)
Weight:	2.5 lbs. (without modules)
Construction:	Powder Coated Aluminum, Off-White Finish
Module Capacity:	3
Fiber Management:	Slide out tray for convenient access to modules and fiber slack storage area


### **LiteVu 2RU Chassis**

Dimensions:	3.5”H x 17”W x 14”D (front fiber management tray projects forward additional 5”)
Weight:	3.5 lbs. (without modules)
Construction:	Powder Coated Aluminum, Off-White Finish
Module Capacity:	4
Fiber Management:	Fiber management is integrated into the chassis




# Product Dimensions

## LiteVu 1.5RU Chassis



## LiteVu 2RU Chassis



## LiteVu Optical Tap Module

Parameters	Value	Unit
Operating Wavelength	1310 & 1550	nm
Insertion Loss (1310/1550)	$\leq 4.8\text{dB}$ (40%), $\leq 3\text{dB}$ (60%) $\leq 1.1\text{dB}$ (90%), $\leq 11.2\text{dB}$ (10%)	dB
PDL	$\leq 0.15$	dB
Directivity	$\geq 55$	dB
Return Loss	$\geq 50$	dB
Tap Ratio	40/60 90/10	
Operating Temp	-40 to +65	°C



## Ordering Information

### LiteVu Chassis

Part #	NEQ #	Description
CFLV-C03U15	NEQ.20231	1.5RU LiteVu Chassis, 3 optical tap module positions
CFLV-C04U02A	NEQ.20232	2RU LiteVu Chassis, 4 optical tap module positions

### LiteVu Monitoring Module

Part #	NEQ #	Description
CFLV-MTRDBXXX11	NEQ.20233	LiteVu optical tap module with 12 LC/UPC monitoring ports



INNOVATIVE ENCLOSED SOLUTIONS™



## Dependable Solutions, Superior Support

- Field-proven and unequaled 24-hour technical support
- Individualized application consultation
- Superior quality (ISO 9001/TL 9000 registered)

Visit our website at <http://www.charlesindustries.com>

Charles Industries, Ltd. Voice: (847) 806-6300  
 Telecommunications Group Fax: (847) 806-6231  
 E-mail: [mktsserv@charlesindustries.com](mailto:mktsserv@charlesindustries.com)



D-OSP175-G17