


Amphenol Charles Industries (ACI) Fiber Distribution & Repair Closures (FDRCV2) are very compact units. They can be used as a repair closure or a small splice closure for a single fiber cable. There are two in-line ports that can accommodate cables or micro-duct up to 7.5mm in diameter as well as commonly used 8 x 4.5mm flat drop cable.


The units have six internal splice slots and can accommodate up to 12 single fusion splices. They feature grommet sealing and can be re-entered and re-sealed. The closures can be direct buried as well as placed in a hand-hole, mounted on a wall, or on an aerial strand.



FDRCV2

## FEATURES

- Compact size: 7" x 5" x 0.9"
- Two in-line cable ports for 3 – 7.5mm cables
- Up to 12 splices
- Re-enterable and resealable
- Can be direct buried, or used in hand-holes, pedestals, as well as wall or aerial mounted
- IP68 rated




# Product Specifications

Material	Glass-filled Polypropylene
Weight	Approx. 1 lb.
Dimensions	7.1" x 5.1" x 0.9" (180 x 129 x 24 mm)
Cable Ports	Two inline ports accommodate 3 – 7.5mm round and flat drop
Splice Capacity	6/12 (double stacked)
Sealing	Compressed silicone grommet augmented with gel-tape
Mounting	Direct buried, hand-hole, pedestal, wall, aerial strand mounted
Rating	IP68

## Outline Dimensions

### DIMENSIONAL VIEWS

All dimensions are in inches



### ORDERING INFORMATION

Part Number	Description	Carton Qty.
FDRCV2P6S	Fiber sealed drop repair closure with 6 splice slots	40


Contact Amphenol Charles Industries for additional available part numbers.

### Charles Industries, LLC

An Amphenol Company

1450 American Lane, 20th Floor, Schaumburg, IL 60173

 [mktserv@charlesindustries.com](mailto:mktserv@charlesindustries.com)

 (847) 806-6300

