


Dome Closures for FTTX Applications

Charles Fiber Optic Dome Closures (FODC) provide a versatile solution for splicing and protecting outdoor fiber connections in a familiar dome form. FODC units can be deployed to support a variety of topologies, including strand, pole mountings, and below-grade vault placements. These closures use compression grommet technology to provide an easy-to-use economical cable sealing solution. Charles offers two sizes of FODC and accommodates up to 144 (FODC-A) or 288 (FODC-B) single fusion fiber splices.

The FODC-A unit is also available with a deeper tray for use with ribbon fiber cables. These trays can accommodate up to 8 ribbons per tray and two trays can fit in a closure for a total of 196 mass fusion splicing.



Fiber Optic Dome Closures

FEATURES


- Robust UV-stabilized glass-filled polypropylene housing
- Available in two sizes- 144 (FODC-A) or 288 (FODC-B) splice capacity
- Units can accommodate single fusion and ribbon fiber splicing
- Fiber splice trays and cable ingress/egress grommets are included
- Closures are aerial, pole, wall or below-grade mountable for flexible placements
- Environmentally sealed and IP 68 rated for below grade deployment

MARKETS SERVED:

- ☒ Telecom / FTTX
- ☒ Utility
- ☐ Wireless
- ☒ Broadband Cable



*Fiber Basket expresses
144 Fiber Cable*



*Splice Trays with fiber
management & slack
storage*





*Hinged Splice Trays have
a lock-in place feature*

FODC-A Product Specifications

Model	FODC-A
External Dimensions	20.5" x 8.9" (520 x 225 mm)
Weight	9.2 lbs. (4.2kg)
Ambient Temperature	-40°F to +149°F (-40°C to +65°C)
Splice Trays	Four (4) 36 Fiber Splice Trays included
Splice Capacity Single Fusion	144 Splices (double stacked)
Splice Capacity Mass Fusion	196 (with FODCARBTRAY)
Feed Cable Port Accommodation	0.315" – 0.71" O.D. (8 – 18 mm)
Four Branch Port Cable Entries	Each port can accommodate 0.315" – 0.71" (8 – 18 mm) cable or multiple smaller cables per port. See ordering information for grommet options
Grounding	Optional version with bond connectors and ground wires
Mounting	Optional pole or aerial mounting kits available, sold separately

FODC-A Dimensions



FODC-A Splice Tray






Base Cable Entries

FODC-B Product Specifications

Model	FODC-B
External Dimensions	24" x 10.2" (610 x 260 mm)
Weight	11 lbs. (5kg)
Ambient Temperature	-40°F to +149°F (-40°C to +65°C)
Splice Trays	Six (6) 48 Fiber Splice Trays included
Splice Capacity Single Fusion	288 Splices (triple stacked)
Feed Cable Port Accommodation	0.315" – 0.785" O.D. (8 – 20 mm)
Four Branch Port Cable Entries	Each port can accommodate 0.315" – 0.71" (8 – 18 mm) cable or multiple smaller cables per port. See ordering information for grommet options
Grounding	Optional version with bond connectors and ground wires
Mounting	Optional pole or aerial mounting kits available, sold separately

FODC-B Dimensions



FODC-A Splice Tray



Base Cable Entries

Ordering Specifications

Part Number

FODCA144BCEFN

FODCA144BG

FODCARBG

FODCB288BCDEFN

FODCB288BG

97-FODCPLKTA

97-FODCPLKTB

97-FODCAMKT

97-FODCAGR

97-FODCARBTRAY

97-FODCBGR

97-FODCCGR

97-FODCDGR

97-FODCEGR

97-FODCFLGR

97-FODCHGR

Description

144 splice capacity dome closure with 4 splice trays and sealing components

144 splice capacity dome closure with 4 splice trays and sealing components, includes 4 shield bond connectors & 4 ground wires

Dome closure with 2 deep FODC-A splice trays for ribbon fiber, 8 ribbon slots per tray, ribbon accessories, ground kit

288 splice capacity dome closure with 6 splice trays and sealing components

288 splice capacity dome closure with 4 splice trays and sealing components, includes 4 shield bond connectors & 4 ground wires

Pole mount kit for FODC-A with brackets and bands

Pole mounting kit for FODC-B with brackets and bands

Aerial mount kit for FODC-A & FODC-B

Grommet kit: 1-hole 13-17mm, bag of 10

Deep ribbon fiber tray for FODC-A

Grommet kit: 1-hole 8-14mm, bag of 10

Grommet kit: 4-hole 5-7mm, bag of 10

Grommet kit: 4-hole 5mm, bag of 10


Grommet kit: 9-hole 3-4mm, bag of 10

Grommet kit: 2-hole 8x4.5mm, bag of 10

Grommet kit: 2-hole 6-8mm, bag of 10



97-FODCPLKTA



97-FODCAMKT

Please contact your Charles representative for addition configurations

Grommet Options

Branch Port Grommet			
Label	View	Cable Sizes	Ordering Number
A		1-hole 13-17 mm	97-FODCAGR
B		1-hole 8-14 mm	97-FODCBGR
C		4-hole 5-7 mm	97-FODCCGR
D		4-hole 5 mm	97-FODCDGR
E		9-hole 3-4 mm	97-FODCEGR
F		2-hole 8 x 4.5 mm	97-FODCFLGR
H		2-hole 6-8 mm	97-FODCHGR

Grommet kits come 10 grommets and end plates to a bag

Charles Industries, LLC

An Amphenol Company

1450 American Lane, 20th Floor, Schaumburg, IL 60173



mktserv@charlesindustries.com



(847) 806-6300

