Splice Closure
Reference Guide

Series	View	Dimensions	Cable Ports	Drop Ports	Splice Capacity	Adapters	Optics Options	Cable Sealing	Rating	Deployment	Notes
Terminal Splice Closures											
FSDCS4P		9.9" x 4.8" x 3.4"	3 ports 6-14mm	4	24/48	4 SC/APC simplex4 SC/APC duplex	Optional SKU with splitters available	Gel Block	IP68	BGE, pedestal, wall, strand	Use with micro-cable & flat feed. Option for 8 drops
FSDCS12P		14.5" x 8.4" x 4.6"	4 ports 6-18mm	12	144	12 SC/APC	Optional SKU with splitters available	Gel block	IP68	BGE, pedestal, wall, strand	Separate door for drop ports. Store 144F LBT
FSDCG		15.1" x 9.6" x 5.1"	4 ports 8-18mm	16	48	16 SC/APC	Optional SKU with splitters available	Grommet	IP68	BGE, pedestal, wall, strand	Protected cover for drop ports. Store 144F LBT
FSDCM		10.1" x 6.6" x 3.4"	2 ports 8-18mm	8	24	8 SC/APC	Optional SKU with splitters available	Grommet	IP68	BGE, pedestal, wall, strand	Use with 24F LBT or flat feed
FSDCH		15.1" x 9.6" x 5.1"	2 ports 8-18mm	2, 4, or 8 OptiTap compatible	48	N/A	Optional SKU with splitters available	Grommet	IP68	BGE, pedestal, wall, strand	Store 144F LBT
FISCH		14.2" x 7.9" x 5.7"	3 ports end 3 - 16 mm	2, 4, 8, 12, 16 OptiTap compatible	72	N/A	Optional SKU with splitters available	Grommet Gel tape	IP68	BGE, pedestal, wall, strand	Store 144F LBT

L-OSP020-I26

Charles Industries, LLC, An Amphenol Company
(847) 806-6300
mktserv@charlesindustries.com

INNOVATIVE ENCLOSED SOLUTIONS

®2026 Charles Industries, LLC • All Rights Reserved

Series	View	Dimensions	Cable Ports	Drop Ports	Splice Capacity	Adapters	Optics Options	Cable Sealing	Rating	Deployment	Notes
Repair & Splice Closures											
FDRCV2		7" x 5" x 0.9"	2 inline 3-7mm & flat	2	12	Optional SC/ APC	N/A	Grommet Gel tape	IP68	BGE, wall, strand, direct buried	reenterable & resusable
FDRC4		9" x 7.2" x 1.7"	4 inline 3- 10mm	2	Up to 48 ribbon option	Adapter holder option	N/A	Grommet Gel tape	IP68	BGE, wall, strand, direct buried	Optional clips for adapter, splitter, or ribbon splices
FORC		11.6" x 8.7" x 3.5"	2 express 8 - 18mm 2 branch 3-18mm	Up to 4 flat/ 8 round	36	N/A	N/A	Grommet	IP68	BGE, wall, direct buried	Store 72F LBT
Dome Closures											
FODCA		20.5" x 7.5" (8.9" with clamp)	2 express 8-18mm 4 branch 3-18mm	up to 8 flat/ 16 round	144 single 196 mass	N/A	N/A	Grommet	IP68	BGE, Pedestal, strand, cabinet	Use deep trays for ribbon. Ribbon tray can hold splitter
FODCB		24" x 8.6" (10.2" with clamp)	2 express 8-22mm 6 branch 3 -18mm	up to 12 flat/ 24 round	288 single 288 mass	N/A	N/A	Grommet	IP68	BGE, Pedestal, strand, cabinet	Same tray LBT or ribbon
FODCC		26" x 10.5" (11.8" with clamp)	2 express 8-26mm 4 branch 3 -20mm	up to 12 flat/ 24 round	960 single 1152 mass	N/A	N/A	Grommet	IP68	BGE, Pedestal, strand, cabinet	Use deep trays for ribbon. Ribbon tray can hold splitter
Aerial Closures											
CFAS		25.3" x 8.5" x 5.4"	3 each end 8-35mm	12	Up to 48	12 SC/APC	Optional splitter/tap trays	Grommet	Free breathing	Aerial strand	Store 72F LBT BEAD BABAA compliant

Charles Industries, LLC, An Amphenol Company
(847) 806-6300
mktserv@charlesindustries.com

INNOVATIVE ENCLOSED SOLUTIONS

®2026 Charles Industries, LLC • All Rights Reserved